



WILD STONE
Politických vězňů 1337, Slaný, Czech Republic
Tel.: +420 312 520 159
Fax: +420 312 523 104
E-mail:
info@wildstone.
www.wildstone.cz

WILD STONE PN

Dispersion bonding primer for the treatment of non-standard surfaces.

Properties

- for immediate use
- it does not contain solvents
- for internal environment
- ideal consistency

Fields of application

WILD STONE PN is a coating suitable for the treatment of non-absorbent, smooth and dense substrates, for substrates with absorbed adhesive residues. Thanks to the content of special additives, it forms an adhesive bridge on the substrates and increases the adhesion of cement materials. Ready to use.

Composition

Dispersion of styrene acrylate copolymer with organic and inorganic additives.

Specifications

colour	pink
yield	3-6 m ²
packing:	3 kg
drying time	3-12 hours

Storage and warranty period

Store in closed containers at temperatures of +5°C to +28°C. Protect from frost and direct sunlight. Under these conditions, it retains the declared properties for 12 months from the date of manufacture. Remove the skin generated from prolonged storage.

Substrate preparation

The substrate must be solid, clean, and permanently dry. Stone substrates, ceramic tiles, terrace must be thoroughly degreased first, washed with warm water and dry. **Residues of old adhesives or bitumen should be removed as much as possible.**

Working process

WILD STONE PN must thoroughly mixed before use, and then applied to the substrate undiluted by brushing or rolling. The resulting puddles must be spread. The coating must be completely dry before applying the levelling compound. After drying, WILD STONE PN forms a continuous, flexible, water-insoluble film. The recommended processing temperature is 5-25°C. All used tools are washable with water before drying. Apply the levelling compound after the coating has completely dried.

Safety measures

- Although WILD STONE PN is non-toxic, it can irritate the skin if repeated and prolonged contact occurs.
- Protect eyes and skin from splashes, use suitable protective equipment during work, observe the principles of personal hygiene.
- Keep away from children!
- Unused residues are disposed of by using normal procedures (incinerators, landfills). Dried residues according to Waste Catalogue, catalogue no. 08 04 10 and category O. Take the empty packaging to separate waste collection points for recycling. According to Waste Catalogue, catalogue no. 15 01 02 and category O.

First aid

In case of contact with skin, wash it with soap and water, in case of contact with eyes, rinse them with water for 10-15 minutes, if accidentally swallowed, rinse mouth with water and drink about half a litre of water. In all serious cases of health damage seek medical attention.

Certificate

WILD STONE PN assessed by TZUS ČESKÉ BUDĚJOVICE s.p. (AO 204) no. 020-023689 of 2 April 2013.

Warning: The manufacturer fully guarantees the quality of the product as set out in PN 301506. Because it does not affect the conditions of processing and professional execution of the work, it cannot assume responsibility for the final quality of the work. Under the given conditions, it is recommended to carry out a practical test in advance.

The manufacturer reserves the right to change the text. With this version, all previous texts expire.